

# PORTABLE AUDIO SYSTEM



**SY-120**



## Technical Indicator

### INPUT SPECIFICATIONS:

- \*4-LINE MICROPHONE /LINE INPUT
- MIC INPUT IMPEDANCE 600 OHMS INPUT LEVEL -60dB
- LINE INPUT IMPEDANCE 47K OHMS INPUT LEVEL -20dB
- 4-LINE MIC +48V PHANTOM POWER
- \*TAPE INPUT
- INPUT IMPEDANCE 47K OHMS INPUT LEVEL -20dB
- \*16-BAND DIGIT EFFECTS
- \*DAUL 5-BANE GRAPHIC EQUALIZER
- \*DAUL 5-BAND LED LEVEL DISPLAY
- \*EFFECTS RETURN FEEDBACK INPUT

### OUTPUT SPECIFICATIONS:

- \*STEREO HEARPHONES OUTPUT
- OUTPUT POWER 300mW
- \*RECORD OUTPUT
- OUTPUT IMPEDANCE 600 OHMS OUTPUT LEVEL -10 dB
- \* EFFECTS SEND
- \*STEREO POWER AMPLIFIER OUTPUT
- OUTPUT POWER 120 WATT 8 OHMS

### SPEAKER

- \*AUDIO SPEAKER INPUT IMPEDANCE 8 OHMS X2
- \*POWER: 80 WATT
- \*FREQUENCY RESPONE: 60 Hz TO 20 KHz